
APPROVA	AL - CUSTOMER NAME & SIGNATU	JRE DATE
ASSEMBLY PART N 2. U-SPRING: 302 S 3. TORSION SPRING 4. SPIROL PIN: SA 5. LOCKWASHER: SP	AND TRIGGER: DIE CAST ZINC, SEE NUMBER TABLE. STAINLESS STEEL, PASSIVATED. : 302 STAINLESS STEEL, NATURAL. E 51420, NATURAL RING STEEL, ZINC ALLOY PLATE BRIGHT PLUS SE NUT: LOW CARBON STEEL,ZINC ALLOY PLATE BRI NUT: LOW CARBON STEEL,ZINC ALLOY PLATE BRI	GHT PLUS SEALER.
7 BRACKET: 1010	STEEL ZING ALLOY PLATE BRIGHT PLUS SEALER	
7. BRACKET: 1010 S B. MOUNTING SCREW AS	STEEL, ZINC ALLOY PLATÉ BRIGHT PLUS SEALER. SSEMBLY CONSISTS OF: M5 SCREW WITH LOCKWASH S (NOT SUPPLIED) FOR THICKER DOORS.	



		84 WHEN ADJUSTED TO MAXIMUM GRIP	
	46mm MAX GRIP	-	
RUBBER BUMPER OPTION P/N C2-25-301-82 (ORDER SEPARATELY)	23mm THRU 43.5mm WITH NUT ON OTHER SIDE OF THE LEVER 42.9mm MAX GRIP WITH BUMPER OPTION	M5 ADJUSTING 7 SCREW	FRAME —
LEVER	LLE	JAM NUT 7 5mm MIN 11mm MA	
LEVER	R IN RAISED I) POSITION	RUBBER BUMPER OPTION	
93	THINK		DOOR
	TRIGGER	MOUNTING SCREW ASSEMBLY SEE NOTE C  MOUNTING BRACKET SEE NOTE C	
34 ————————————————————————————————————	1mm MIN DOOR THICKNESS — F	HOUSING	4X R3 MAX 25±1
WIDIH		22 —	PANEL PREPARATION

ALLEGIS	1-866-378-7550
MATERIAL:	DRAWING NO.:
Zinc Alloy	C2-33-35
FINISH:	•
Powder Coat	
REV.: 1:1	DATE: 5/29/2019