

PAWL IN OPEN POSITION.  
RIGHT HAND OPERATION SHOWN.

KNOB STYLE

80°

Ø 21

23

INDICATOR MARKS ON RIM ALIGN WITH KNOB, WHEN PAWL IS IN FULLY LATCHED POSITION.

OPTIONAL FLANGE GASKET E3-0-30268-02 SOLD SEPARATELY

A

A

13 MAX DOOR THICKNESS

LOCKWASHER

MOUNTING NUT

GRIP SEE TABLE

LATCH SUBASSEMBLY

2X LOCKWASHER

PAWL

2X M6 NUT

4.3 PULL UP

16  
+0.2  
-0.0

16

6

21.5

37

PANEL PREPARATION SCALE 1:1


FRAME

17.5 ± 1.5

DOOR

13.5  
+0.2  
-0.0

GRIP	MINIMUM	MAXIMUM
0	NO CAM	
2	6.4	9.5



5 - SOUTHCO TUBULAR KEY  
(USE SOUTHCO KEY E3-26-819-15)

[www.allegiscorp.com](http://www.allegiscorp.com)

1-866-378-7550

MATERIAL / FINISH:

Black powder coated Zinc alloy

REV.:

Rev. 1

SCALE:

1:1

DATE:

9-20-2024

DESCRIPTION:

Compression Latch

DRAWING NO.:

E3-55-25